

Application No. 10/789,930

Filed: February 27, 2004

TC Art Unit: 1722

Confirmation No.: 6805

AMENDMENT TO THE CLAIMS

1. (Currently Amended) A blow molding machine comprising
a plurality of pillars set up facing on a seat on a base
located above a blow mold;
a stationary platen provided bridging on the top portions of
the pillars;
a moving cylinder set ~~on both side~~ on both sides of the
stationary platen; and
a holding plate of blow-core ~~members, which~~ members, which
is connected with a piston rod of the moving cylinder, and in
which the pillars are inserted vertically movable;
and a clamp plate projecting at both ends from the holding
plate outwardly,
and a clamp block, which includes internally a pair of
hydraulic cylinders to clamp the clamp plate from both sides with
rams when the holding plate is in the lower limit position, which
is provided on both sides of the seat.
2. (Currently Amended) The blow molding machine of claim 1,
wherein a movable platen provided under the stationary platen is
connected to the piston rod, and a tie rod, which is set
lengthways under the movable platen, is connected to the holding
plate, and a ~~set plate of stretch~~ plate for a stretch rod is kept
vertically movable by the tie rod, which is inserted through the
set plate, and the set plate is connected to a plunger of a

Application No. 10/789,930
Filed: February 27, 2004
TC Art Unit: 1722
Confirmation No.: 6805

stretch driving means which is provided to the movable platen
longitudinally in the center.